

COOLTOUCH RX-1701A

Rack-Mounted 17" LCD Multimedia Monitor with Integrated Audio



- Single 17.0" LCD Video Monitor
- 1280 x RGB x 1024 Pixels
- 300 cd/m², 700:1 Contrast, 8ms Response
- One Composite, 1 RGB Analog & 1 S-Video In
- NTSC / PAL autosensing
- One Analog Stereo Audio Input
- Integrated Audio Confidence Monitor
- Tri-Color LED Contact Closure Tally
- 8 Rack Units Tall, 2.4" / 61mm Deep Chassis

Offering superb quality, yet at a highly cost effective price, the RX-1701A 4:3 17" rack mount monitor includes 1 composite video, 1 VGA/analog RGB (RGBHV) and 1 S-Video inputs and offers excellent picture quality even under high ambient light conditions with 300nits of brightness and a 700:1 contrast ratio. An analog audio stereo input feeds the built-in speakers that can be used as a confidence monitor or audible alarm from an external source. Designed for broadcasters and other professionals who need to be able to monitor fast moving video, the RX-1701A offers an extremely fast response time of just 8ms.

LCD Diagonal	LCD Size	No. of LCDs	Resolution*	Aspect Ratio	Dot pitch	Viewing Angles	Backlight	Rack Size	Dimensions: US	Dimensions: Metric	Weight*
17" / 432 mm	338 x 270mm	1	3840 x 1024	4 : 3	0.264 x 0.264mm	135 / 150 degrees	50k hours	8	19 x 13.9 x 2.4"	483 x 353 x 61mm	13lbs (5.9kg)

MODEL	INPUTS					OUTPUTS			Brightness	Contrast	Touch Screen	Weather Proof	Audio	Power
	Composite	VGA	S-Video	SDI	Analog Audio	Composite	SDI	Analog Audio						
RX-1701A	1	1	1	-	1	1 (active loop)	-	-	300	700 : 1	-	-	Yes	90-240VAC, 50W

CoolTouch Monitors LLC

P.O. Box 10771 - Marina del Rey, CA 90295 - Tel: (310) 923-1354 - Fax: (310) 392-3510
 info@cooltouchmonitors.com - www.CoolTouchMonitors.com