

# COOLTOUCH RX-563ALS

**Triple 5.6" LCD Multimedia Monitor with Integrated Audio**  
*with composite video & analog audio loopthrough*



- Three 5.6" LCD Video Monitors
- 960 x 234 Pixels, 350 cd/m<sup>2</sup>, 250:1 Contrast
- Two Composite Video Inputs - per screen
- Loop-Through Output of Video & Audio
- NTSC / PAL autosensing
- One Analog Audio Input - per screen
- Integrated Audio Confidence Monitor
- 3 Rack Units Tall, 2.1" / 53mm Deep Chassis

Offering superb quality, yet at a highly cost effective price, the RX-563ALS triple 5.6" rack mount monitor includes one audio and two composite video inputs - per screen and offers excellent picture quality even under high ambient light conditions. Each screen has discreet audio with built-in speakers that can be used as a confidence monitor or audible alarm from an external source. Loop-through outputs of the Audio & Video inputs is provided. Powered by only 12VDC (power supply included), and designed to give reliable performance in the field, the RX-563ALS offers great service at a great price.



LCD Diagonal	LCD Size	No. of LCDs	Resolution*	Aspect Ratio	Dot pitch	Viewing Angles	Backlight	Rack Size	Dimensions: US	Dimensions: Metric	Weight*
5.6" / 142mm	115 x 87mm	3	960 x 234	4 : 3	0.116 x 0.348mm	60 / 130 degrees	10k hours	3	19.1 x 5.1 x 2.1"	485 x 130 x 53mm	5 lbs (2.3kg)

MODEL	INPUTS					OUTPUTS			Brightness	Contrast	Touch Screen	Weather Proof	Audio	Power
	Composite	VGA	S-Video	SDI	Analog Audio	Composite	SDI	Analog Audio						
RX-563ALS	6	3	-	-	3	6 (passive loop)	-	3 (loop)	350	250 : 1	-	-	Yes	3A at 12VDC

## CoolTouch Monitors LLC

P.O. Box 10771 - Marina del Rey, CA 90295 - Tel: (310) 923-1354 - Fax: (310) 392-3510  
 info@cooltouchmonitors.com - www.CoolTouchMonitors.com