

COOLTOUCH RX-563SDI

SDI Triple 5.6" LCD Multimedia Monitor with Integrated Audio
with tally and 10 bit encoded composite output from SDI



- Three 5.6" LCD Video Monitors
- 960 x 234 Pixels, 350 cd/m², 250:1 Contrast
- One SDI Input - per screen
- One Composite Video Inputs - per screen
- 10 Bit Encoded Composite output from SDI
- Loop-Through Output of Composite Video
- 525 / 625 & NTSC / PAL autosensing
- One Analog Audio Input - per screen
- Integrated Audio Confidence Monitor
- Tri-Color LED Contact Closure Tally
- 3 Rack Units Tall, 2.1" / 53mm Deep Chassis

The RX-563SDI triple 5.6" rack mount monitor includes one audio, one SDI input and two composite video inputs - per screen. A high quality tally light system is included and operates via contact closures. Each screen has discreet audio with built-in speakers that can be used as a confidence monitor or audible alarm from an external source. Powered by only 12VDC (power supply included), and designed to give reliable performance in the field. This is the only multiple screen SDI monitor of its kind to offer an integrated audio confidence monitoring system, and with a total chassis depth of only 2.1" (53mm), it also offers the shallowest depth in its class.



LCD Diagonal	LCD Size	No. of LCDs	Resolution*	Aspect Ratio	Dot pitch	Viewing Angles	Backlight	Rack Size	Dimensions: US	Dimensions: Metric	Weight*
5.6" / 142mm	115 x 87mm	3	960 x 234	4 : 3	0.116 x 0.348mm	60 / 130 degrees	10k hours	3	19.1 x 5.1 x 2.1"	485 x 130 x 53mm	5 lbs (2.3kg)

MODEL	INPUTS					OUTPUTS				Brightness	Contrast	Touch Screen	Weather Proof	Audio	Power
	Composite	VGA	S-Video	SDI	Analog Audio	Composite	SDI	Analog Audio							
RX-563SDI	3	3	-	3	3	6 (3 from SDI, 3 passive loop)	3 relocked	-	350	250 : 1	-	-	Yes	3.7A at 12VDC	

CoolTouch Monitors LLC

P.O. Box 10771 - Marina del Rey, CA 90295 - Tel: (310) 923-1354 - Fax: (310) 392-3510
 info@cooltouchmonitors.com - www.CoolTouchMonitors.com