


# COOLTOUCH RX-802AL

**Dual 8" LCD Multimedia Monitor with Integrated Audio**  
*with composite video loopthrough*



- Two 8" LCD Video Monitors
- 1920 x 480 Pixels, 400 cd/m<sup>2</sup>, 400:1 Contrast
- Two Composite Video Inputs - per screen, w/loop
- One VGA Input - per screen
- One S-Video Input - per screen
- One Analog Audio Input - per screen
- Integrated Audio Confidence Monitor
- 4 Rack Units Tall, 2.2" / 56mm Deep Chassis

Offering superb quality, yet at a highly cost effective price, the RX-802AL dual 8" rack mount monitor includes one audio, two composite video (with loop-throughs), one S-Video, and one VGA input - per screen and offers excellent picture quality even under high ambient light conditions. The built-in VGA scalar can accommodate resolutions from 640x480 to 1024x768. Each screen has discreet audio with built-in speakers that can be used as a confidence monitor or audible alarm from an external source. The unit is powered by only 12VDC and comes with an 110/240VAC adapter.



**INTEGRATED AUDIO**

**BACK LIGHT LIFE 50,000 HOURS**

**1920 x 480 Pixels**

LCD Diagonal	LCD Size	No. of LCDs	Resolution*	Aspect Ratio	Dot pitch	Viewing Angles	Backlight	Rack Size	Dimensions: US	Dimensions: Metric	Weight*
8" / 203mm	163 x 122mm	2	1920 x 480	4 : 3	0.084 x 0.254mm	120 / 130 degrees	50k hours	4	19 x 6.9 x 2.2"	483 x 175 x 56mm	5 lbs (2.3kg)

MODEL	INPUTS					OUTPUTS			Brightness	Contrast	Touch Screen	Weather Proof	Audio	Power
	Composite	VGA	S-Video	SDI	Analog Audio	Composite	SDI	Analog Audio						
RX-802AL	4	2	2	-	2	4 (passive loop)	-	-	400	400 : 1	-	-	Yes	3.5A at 12VDC

## CoolTouch Monitors LLC

P.O. Box 10771 - Marina del Rey, CA 90295 - Tel: (310) 923-1354 - Fax: (310) 392-3510  
info@cooltouchmonitors.com - www.CoolTouchMonitors.com