

COOLTOUCH RX-802TA

Touchscreen Dual 8" LCD Multimedia Monitor with Integrated Audio



- Two 8" LCD Video Monitors
- One S-Video Input - per screen
- 1920 x 480 Pixels, 330 cd/m², 400:1 Contrast
- One Analog Audio Input - per screen
- Two Composite Video Inputs - per screen
- Touchscreen Interface using USB
- One VGA Input - per screen
- Integrated Audio Confidence Monitor



Offering superb quality, yet at a highly cost effective price, the RX-802TA Touchscreen dual 8" rack mount monitor includes one audio, two composite video, one S-Video, and one VGA input - per screen and offers excellent picture quality even under high ambient light conditions. The built-in VGA scalar can accommodate resolutions from 640x480 to 1024x768. Each screen has discreet audio with built-in speakers that can be used as a confidence monitor or audible alarm from an external source. This unit comes with Linux, Apple and Windows drivers to control the touchscreen interface via the USB port. The RX-802TA is powered by only 12VDC and comes with an 110/240VAC adapter.



LCD Diagonal	LCD Size	No. of LCDs	Resolution*	Aspect Ratio	Dot pitch	Viewing Angles	Backlight	Rack Size	Dimensions: US	Dimensions: Metric	Weight*
8" / 203mm	163 x 122mm	2	1920 x 480	4 : 3	0.084 x 0.254mm	120 / 130 degrees	50k hours	4	19 x 6.9 x 2.2"	483 x 175 x 56mm	5 lbs (2.3kg)

MODEL	INPUTS					OUTPUTS			Brightness	Contrast	Touch Screen	Weather Proof	Audio	Power
	Composite	VGA	S-Video	SDI	Analog Audio	Composite	SDI	Analog Audio						
RX-802TA	4	2	2	-	2	-	-	-	330	400 : 1	Yes	-	Yes	3.5A at 12VDC

CoolTouch Monitors LLC

P.O. Box 10771 - Marina del Rey, CA 90295 - Tel: (310) 923-1354 - Fax: (310) 392-3510
 info@cooltouchmonitors.com - www.CoolTouchMonitors.com